



Carnegie Mellon University

Language Technologies Institute



Could you give me a hint? Generating inference graphs for defeasible reasoning

**Aman Madaan*¹, Dheeraj Rajagpoal*¹, Niket Tandon*²
Yiming Yang¹, Eduard Hovy¹**

* Equal contribution, 1: Language Technologies Institute, Carnegie Mellon University, 2: Allen Institute for AI

https://github.com/madaan/defeasible_graphs

Outline


I. Defeasible Reasoning

**Generating inference graphs
for defeasible reasoning**

II. Generating graphs for defeasible reasoning queries

Defeasible Reasoning

- Given a premise **P**, a hypothesis **H** may be weakened or strengthened (revised) with new evidence (update) **U**



Thinking Like a Skeptic: Defeasible Inference in Natural Language

Rachel Rudinger^{†‡§}, Vered Shwartz^{†‡}, Jena D. Hwang[†], Chandra Bhagavatula[†],
Maxwell Forbes^{†‡}, Ronan Le Bras[†], Noah A. Smith^{†‡}, Yejin Choi^{†‡}

[†]Allen Institute for AI

[‡]Paul G. Allen School of Computer Science & Engineering, University of Washington

[§]University of Maryland, College Park, MD



J. Pollock. 1987. Defeasible reasoning. *Cogn. Sci.*, 11:481–518.

Improving Defeasible Reasoning with additional information

- Humans often have difficulty in this task [Rudinger et al, 2020]
- Idea: Adding information to defeasible query might be helpful

Key contributions and findings:

1. Method for automatic construction of inference graphs.
2. Human evaluation finds these graphs useful for defeasible reasoning.



Outline

I. Defeasible Reasoning

II. Generating graphs for defeasible reasoning queries

Generating inference graphs for defeasible reasoning

WIQA

- A corpus of 2100 (passage, graph) pairs


WIQA: A dataset for "What if..." reasoning over procedural text

Niket Tandon*, Bhavana Dalvi Mishra*, Keisuke Sakaguchi,
Antoine Bosselut, Peter Clark
Allen Institute for Artificial Intelligence, Seattle, WA
{nikett,bhavanad,keisukes,antoineb,peterc}@allenai.org

Erosion by the ocean:

1. Wind creates waves in the ocean.
2. The waves wash onto the beaches.
3. The waves hit rocks on the beach.
4. Tiny parts of the rock break off.
5. The rocks become smaller.

P: A contagious virus is spreading



Generating inference graphs for defeasible reasoning

Training on WIQA

Erosion by the ocean:
1. Wind creates waves in the ocean.
2. The waves wash onto the beaches.
3. The waves hit rocks on the beach.
4. Tiny parts of the rock break off.
5. The rocks become smaller.

Passage

+



Erosion by the ocean rocks quickly becomes smaller

Hypothesis

+

The wind is blowing harder


Situation



Generating inference graphs for defeasible reasoning



Inference on Defeasible

- Given a new query *PHU*, run inference on graph generator trained on WIQA to obtain an influence graph




Do humans find these graphs useful for defeasible reasoning?

- For the same human pool from Rudinger et al, 2020, we show defeasible inference questions along with the generated inference graphs.
- Each question was answered by 3 annotators and majority was taken as the chosen answer



Do humans find these graphs useful for defeasible reasoning?



● Mediator ● Extraneous ● Structure ● None helpful

- Different parts of the graph were found to be useful to a different degree

Model-generated graphs help humans at Defeasible Reasoning!

Graphs available here: https://github.com/madaan/defeasible_graphs